


Typical Device Performance (25°C)

	Unit	Typical Value
Optical		
CW Output Power	W	20
Center Wavelength	nm	808±3
Spectral Width (90% of Power)	nm	<3.0
Wavelength Shift with Temperature	nm / °C	0.3
Electrical		
Threshold Current	A	1.8
Operating Current	A	10.5
Operating Voltage	V	3.5
Slope Efficiency	W / A	2.2
Power Conversion Efficiency	%	50
Fiber		
Fiber Core Diameter	μm	400
Fiber Cladding Diameter	μm	440
Fiber Buffer Diameter	μm	700
Numerical Aperture	-	0.22
Fiber Length	m	1.0
Fiber Connector	-	SMA905


Absolute Ratings

	Unit	Min	Max
Operating Temperature	°C	10	40
Operating Relative Humidity	%	-	75
Storage Temperature	°C	-20	80
Storage Relative Humidity	%	-	90
Lead Soldering Temperature, 10 s max	°C	-	250




Characteristics of 808nm-18W laser diode module (25°C)



Typical spectrum of 808nm-18W laser diode module (25°C)




Package Dimensions (mm)



Pin Assignment	
Pin	Function
1	LD (+)
2	LD (-)

Type Definition



* Accessory: T – TE cooler, A – Aiming Laser, P – Monitor photo diode, K – Fiber connector Detector

* Package: T1, T2, T3, T4, T4S, T4T, T6, G4, C1, D1.....

* Fiber or Connector: F – Fiber Output, D – Detachable Connector

